

Oldomat 20

Machine dishwashing detergent



Properties

- containing chlorine
- phosphate-free
- alkaline
- for higher water hardness

Application

Oldomat 20 is an intensive alkaline detergent for use in automatic dishwashers. Oldomat 20 is foam-free, hydrolysis-resistant and contains a cleaning booster based on active chlorine. When using the product, there is no discoloration of steel. This product is not suitable for aluminum parts. Oldomat 20 is used in all areas of industry and commerce as an intensive cleaner for automatic dishwashers. The product is used with hard process water (over 10°dH). Oldomat 20 is added via the automatic control and dosing system of the dishwasher or directly into the machine or the dosing device provided for this purpose before cleaning begins.

Dosing

Dishwashers

Concentration	2,5 - 5,0 ml / l water
Temperature	gemäß Maschinentakt
Exposure time	gemäß Maschinentakt
Addition	The dosage depends on the water quality and degree of soiling, and after treatment with cleaning products, always rinse with fresh water to completely remove all products from the cleaned surfaces.

Technical data

Density (20°C)	pH-value
1,18 kg / l	12 ; 1 %

Titration

Prepare 10 ml application solution, fill with approx. 100 ml dist. Water and add a spatula tip of sodium thiosulphate. Titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.
Consumption (ml) x 0.44 = concentration in %

Notes

Storage:

Store the product only in the original container and in a frost-free place between +5 and +20°C. Avoid direct sunlight. Please reseal the container tightly after removing partial quantities.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.