

# Tolo SW

## Detergent for washing boots

### Properties

- removes protein and fat effectively
- dissolves organic soiling
- stable to water hardness
- phosphate-free

### Application

Tolo SW is a highly alkaline and bleaching cleaning agent for alkali-, moisture- and bleach-resistant footwear. This can be shoes, boots, clogs, etc. made of rubber or plastic. Tolo SW is used in all areas of food processing. Tolo SW is particularly suitable for hygiene sluices in entrance and exit areas as well as intermediate sluices with boot cleaning machines.

Tolo SW is suitable for use on stainless steel (1.4301, 1.4571), iron and alkali-resistant plastics, among others, under the specified conditions.

### Dosing

#### Hygiene sluice, boot washer and manual

Concentration	0,5 - 1,5 %
Temperature	4 - 40 °C
Exposure time	gemäß Bedienungsanleitung

### Technical data

Density (20°C)	pH-value	Conductance (1%; 20°C)
1,20 kg / l	12 - 13 ; 1 %	8,5 ; 1% mS/cm

### Titration

Prepare 10 ml application solution and destroy the chlorine by adding a spatula tip of sodium thiosulphate. Titrate with 0.1 N hydrochloric acid against the indicator phenolphthalein.

Consumption (ml) x 0.27 = concentration in %

### Notes

#### Storage:

Store the product only in the original container and in a frost-free place between +5 and +20°C. Avoid direct sunlight. Please reseal the container tightly after removing partial quantities.

This product is halal certified.

The certification was carried out with reference to the standards "BPJPH Decree No. 20 2023" and "OIC/SMIIC 50-1:2022" in product category K for the production, filling, storage and distribution of cleaning agents and disinfectants.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.