

Truck-Clean HLS

Alkaline intensive vehicle cleaner

Properties

- phosphate-free
- fast wetting
- for brush washing systems, spray and high-pressure devices
- Removes grease, oil and atmospheric soiling

Application

Truck-Clean HLS is an alkaline liquid concentrate and was specially developed for manual or automatic use in brush washing systems and HD/HW devices. Buses, trucks, streetcars etc. are cleaned gently and thoroughly. Stubborn problem dirt is dissolved in a very short time, allowing it to be removed quickly and thoroughly. Truck-Clean HLS can be mixed with water in any ratio. The application concentration depends on the degree of soiling of the vehicles to be cleaned. The solution is sprayed onto the vehicle surfaces to be cleaned from bottom to top using a suitable sprayer or high-pressure device. If necessary, a premix is prepared; the instructions of the device manufacturer must be observed. In the case of stubborn stains, rework with a brush if necessary; after a short exposure time of approx. 3 - 5 minutes, rinse thoroughly - if possible with high pressure. For manual cleaning with a higher application concentration and initial application, a test application should be carried out on a concealed area to check the compatibility of the material. Truck-Clean HLS is the fragrance-free alternative to BÜFA-Clean Extra.

Pre-spray method: 1:10 to 1:50 diluted with water
Washing systems: depending on the system
HD/HW devices: 0.25 - 1.0 % (at the nozzle)
Manual cleaning: 1:10 to 1:100 diluted with water

Technical data

Density (20°C)	pH-value
1,11 kg / l	11,50 - 12,50

Notes

Only store the product in the original container and in a frost-free place.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

The surfactants contained in the product meet the conditions regarding biodegradability as specified in Regulation EC 648/2004 for detergents.

The product does not contain any organic complexing agents that are not sufficiently biodegradable, e.g. EDTA (according to Annex 49 of the Waste Water Ordinance).

Due to the formulation components used, no organically bound halogen compounds (AOX) are contained as active substances.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.