

# SolventClean SP 1

## High-boiling solvent cleaner

### Properties

- label-free
- Very effective: Removes particularly stubborn, dried, cross-linked residues; also PU or PVC.
- Distillable if no water and no strong acidic or basic catalyst is present
- Low-emission, flash point according to DIN EN 22719-A: >100 °C

### Application

SolventClean SP 1 is a high-boiling solvent-based cleaner. It is suitable for direct use in machine cleaning or manual cleaning, for example of preparation containers or parts. Water-based and solvent-based ink systems are cleaned equally well by SolventClean SP 1 even at room temperature. For particularly thick layers with a high degree of cross-linking of the ink systems to be cleaned, manual spraying of the adhesions and an exposure time of approx. 20 minutes is recommended before machine cleaning.

Suitable surfaces: steel, stainless steel, aluminium, aluminium alloys, galvanized material, non-ferrous metals

Only treat after testing: Plastics

Area of application: manual and machine processes

For removal of: water- and solvent-based paint systems (even very stubborn residues of PU, PVC or styrene-butadiene copolymers)

### Technical data

Density (20°C)	pH-value
1,09 kg / l	5 - 6

### Cleaning bath

Flashpoint
> 100 °C (Pensky-Martens DIN EN 22719-A)

### Notes

Only store the product in the original container, tightly closed and dry. After removing partial quantities, please close the container tightly again. Protect from direct sunlight.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.