

Tolo 129 Spezial

Mildly alkaline special cleaning concentrate



Properties

- particularly gentle on the material
- dissolves even persistent stains
- for cleaning workshop floors and pits
- suitable for all common HD/HW devices

Application

Tolo 129 Spezial is a mildly alkaline liquid cleaner. Its combination of active ingredients achieves a particularly rapid dissolution of dirt and gentle treatment of the surfaces to be cleaned. Tolo129 Spezial can also be used with hard process water without any loss of effectiveness. Tolo 129 Spezial can be used in all areas of industry and commerce for basic and maintenance cleaning. It is particularly suitable for use with high pressure, steam or spraying equipment.

Basic cleaning manual: 1 : 5 to 1 : 20 diluted with water

Maintenance cleaning manual: 1 : 20 to 1 : 100 diluted with water

Spraying equipment: 1 : 5 to 1 : 20 diluted with water. A spraying pressure of max. 10 bar should not be exceeded.

HD and steam blasting equipment: 1 : 5 to 1 : 20 diluted with water.

Tolo 129 Spezial can be used with cold water, but the use of warm water significantly improves the cleaning result. Recommended temperature for all types of application: 20 to 60°C. After cleaning with Tolo 129 Spezial in food processing plants, rinse with fresh water to remove all product residues from the cleaned surface.

Technical data

Density (20°C)	pH-value
1,03 kg / l	10,5 ; 1 %

Notes

Storage:

Store the product only in the original container and frost-free.

Direct sunlight should be avoided.

After removing partial quantities, the container should be resealed.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.